

NEW

Now Available for Trimble



Photo Includes Options

Variable Rate Row Crop Spreader

Specification for Row Crop:

- Variable Rate Application using Trimble Rate Control Systems
- Rawson Par 40 Hydraulic Drive System - Gear Box, Sensor, & Hydraulic Control Valve
- Fertilizer and Lime
- All Stainless Hull, Gate, Dishes, Blades, Conveyor
- Conveyor - Clinched, 16" or 24"
- Trailer - 2 x 6 Tubing, Powder Coat Paint
- Body Lengths - Available in 9 or 10 ft, 6 or 7 ton
- Tires - 18.4 x 26 (shown) or 11.25 x 28
- Flotation Tires Available
- Spread Pattern Up to 80 Feet
- Hydraulic Spinners
- Window
- Row Widths Set to Customer Specifications
- Optional - Adjustable Draw Bar Height



NCI Spreaders Compatible with:

- Trimble FmX
- Trimble EZ Guide 500
- Trimble Field IQ System

Variable Rate Available on:

- Row Crop Pull Types
- Tandem Axle Pull Types
- Dry Truck Spreaders
- Self-Propelled Spreaders



Griffin, GA **Sebring, FL**
1-800-241-1350 1-877-605-0273

Albany, GA
1-800-624-7931
www.newtoncrouch.com
sales@newtoncrouch.com