Rollers

A dry spreader has 2 rollers: Front Roller and Rear Roller. They are designed to fit conveyor chain used in NCI spreaders. There are 2 types of conveyor chain: Clinched Pin and Straight Pin. The standard conveyor on a NCI spreader will be either 24" or 16".


In addition to chain width and type, It is important to know what if your unit has a Rawson Gear Box and the size shaft in your roller when placing an order for replacement parts. The best way to ensure correct parts is to have your unit's serial number before calling the Parts

Department.

Rear Rollers and Chain are NOT interchangeable.

Clinched pin chain uses a roller without sprockets near the end of the roller. This is to accommodate the curved ends of the chain.


Straight pin chain uses a roller with sprockets near the end of the roller. This is to engage the entire width of the chain.



The easiest way to determine the conveyor chain on your unit is to count the sprockets on the rear roller.

# of Sprockets	Type of chain		Type of Roller	
7	CA-CBCW16	16" clinched pin chain	CN-015005CR CN-015005CU CN-015005DB	RR, 16", 1½" shaft, Rawson RR, 16", 1½" shaft RR, 16", 2" shaft
9	CA-BCW16	16" straight pin chain	CN-015005S CN-015005T CN-015005V	RR, 16", 1½" shaft, Rawson RR, 16", 2" shaft, Rawson RR, 16", 1½" shaft
11	CA-CBCW24	24" clinched pin chain	CN-015005CO CN-015005DD	RR, 24", 2" shaft, Rawson RR, 24", 2" shaft
13	CA- BC24	24" straight pin chain	CN-015005CE CN-015005U	RR, 24", 2" shaft, Rawson RR, 24", 2" shaft

Standard rollers for the 16" & 24" chains. Other size rollers are available and special orders are accepted.





Front Roller (shown without shaft)

Front Rollers ARE interchangeable and can be used with either clinched or straight pin chains: CN-015005R for 16" chain CN-015005M for 24" chain

Rear Roller Shaft for 24" Straight Pin Chain.



13 Sprockets

Installed Front Roller without Chain



Installed Rear Roller without Chain



Roller shown is for 24" Clinched Pin Chain